

SANYO

No.990C

2SB903/2SD1212

PNP/NPN Epitaxial Planar Silicon Transistors

30V/12A High-Speed Switching Applications

APPLICATIONS

- Suitable for relay drivers, high-speed inverters, converters, and other general large-current switching applications

FEATURES

- Low collector-emitter saturation voltage: $V_{CE(sat)} = (-)0.5V(\text{PNP}), 0.4V(\text{NPN})$ max.
- Large current capacity

Values for 2SB903 shown in ()

ABSOLUTE MAXIMUM RATINGS/ $T_a=25^\circ\text{C}$

			unit
Collector-to-base voltage	V_{CBO}	(-)60	V
Collector-to-emitter voltage	V_{CEO}	(-)30	V
Emitter-to-base voltage	V_{EBO}	(-)6	V
Collector current	I_C	(-)12	A
Collector Current(Pulse)	I_{CP}	(-)20	A
Allowable collector dissipation	P_C	1.75	W
		$T_c=25^\circ\text{C}$	35
Junction temperature	T_j	150	$^\circ\text{C}$
Storage ambient temperature	T_{stg}	-55~+150	$^\circ\text{C}$


ELECTRICAL CHARACTERISTICS/ $T_a=25^\circ\text{C}$

			min	typ	max	unit
Collector cut-off current	I_{CBO}	$V_{CB} = (-)40V, I_E = 0$			(-)0.1	mA
Emitter cut-off current	I_{EBO}	$V_{EB} = (-)4V, I_C = 0$			(-)0.1	mA
DC current gain	$h_{FE(1)}$	$V_{CE} = (-)2V, I_C = (-)1A$	70*		280*	
	$h_{FE(2)}$	$V_{CE} = (-)2V, I_C = (-)6A$	30			
Gain bandwidth product	f_T	$V_{CE} = (-)5V, I_C = (-)1A$		120		MHz
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = (-)5A, I_B = (-)0.25A$			(-0.5)	V
					0.4	V
Collector-base breakdown voltage	$V_{(BR)CBO}$	$I_C = (-)1mA, I_E = 0$	(-)60			V
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	$I_C = (-)1mA, R_{BE} = \infty$	(-)30			V
Emitter-base breakdown voltage	$V_{(BR)EBO}$	$I_E = (-)1mA, I_C = 0$	(-)6			V
Turn-on time	t_{on}	See specified test circuit.		(0.1)0.2		μs
Storage time	t_{stg}	See specified test circuit.		(0.3)0.5		μs
Fall time	t_f	See specified test circuit.		0.03		μs

* 2SB903 and 2SD1212 are graded as follows by h_{FE} at 1A:

70	Q	140	100	R	200	140	S	280
----	---	-----	-----	---	-----	-----	---	-----

Switching time measurement circuit.




(For PNP, the polarity is reversed)

$10I_{B1} = -10I_{B2} = I_C = 5A$
Unit (Resistance: Ω , Capacitance: F)

Package Dimensions 2010B









(unit: mm)








E: Emitter
C: Collector
B: Base

SANYO Electric Co., Ltd. Semiconductor Business Headquarters

TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN





- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.