

JZC-22F-2



CLASSIFICATION	PCB RELAY
Appearance 外型	JZC-22F-2
Outline Dimension(L×W×H) 外形尺寸(mm)	21×16×20.3
Contact Form 触点形式	1A,1B,1C
Contact Resistance 接触电阻	100mΩ
Coil Voltage 线圈电压	3-48VDC
Pick-up Voltage 动作电压	≤75%
Release Voltage 释放电压	≥10%
Coil Power(W) 线圈功率 (瓦)	0.36,0.45
Contact Rating 触点容量	20A/125VAC,28VDC 10A/220VAC
Insulation Resistance 绝缘电阻	100MΩ

Release Voltage 释放电压		≥10%
Coil Power(W) 线圈功率 (瓦)		0.36,0.45
Contact Rating 触点容量		20A/125VAC,28VDC 10A/220VAC
Insulation Resistance 绝缘电阻		100MΩ
Dielectric Strength 介质耐压	Between Open Contact 断开触点间	1000VAC
	Between Coil and Contact 触点线圈间	4000VAC
Life 寿命	Electrical 电气	1×10 ⁵
	Mechanical 机械	1×10 ⁷
Temperature Range 使用温度		-40~+85°C
Terminal Layout 脚位图		
Mounting Holes(mm) 安装尺寸		
Mounting Form 安装形式		PCB
Weight 重量		10g
Safety Approval 安全标准		