


## T73-2



**Terminal Layout**  
脚位图



**Mounting Holes(mm)**  
安装尺寸



|                                   |                                |                      |
|-----------------------------------|--------------------------------|----------------------|
| CLASSIFICATION                    |                                | AUTOMOBILE RELAY     |
| Appearance 外型                     |                                | T73-2                |
| Outline Dimension(L×W×H) 外形尺寸(mm) |                                | 19×15.5×15.5         |
| Contact Form 触点形式                 |                                | 1A,1C                |
| Contact Resistance 接触电阻           |                                | <50mΩ                |
| Coil Voltage 线圈电压                 |                                | 6,9,12,24VDC         |
| Pick-up Voltage 动作电压              |                                | ≤65%                 |
| Release Voltage 释放电压              |                                | ≥10%                 |
| Coil Power(W) 线圈功率 (瓦)            |                                | 0.8W                 |
| Contact Rating 触点容量               |                                | 20A/14VDC 15A/125VAC |
| Insulation Resistance 绝缘电阻        |                                | 100MΩ                |
| Dielectric Strength 介质耐压          | Between Open Contact 断开触点间     | 750VAC               |
|                                   | Between Coil and Contact 触点线圈间 | 1500VAC              |
| Life 寿命                           | Electrical 电气                  | 10 <sup>5</sup>      |
|                                   | Mechanical 机械                  | 10 <sup>7</sup>      |
| Temperature Range 使用温度            |                                | -40 ~ +85℃           |
| Terminal Layout 脚位图               |                                |                      |
| Mounting Holes(mm) 安装尺寸           |                                |                      |
| Mounting Form 安装形式                |                                | PCB Terminal         |
| Weight 重量                         |                                | 10g                  |
| Safety Approval 安全标准              |                                | UL, TUV              |
| Cross-Reference 型号对照              |                                | OMRON G5L            |