

FEATURES


- Fast switching
- 100% avalanche tested
- Improved dv/dt capability

APPLICATIONS

- Switch Mode Power Supply (SMPS)
- Uninterruptible Power Supply (UPS)
- Power Factor Correction (PFC)



TO-247



Absolute Maximum Ratings $T_C = 25^\circ\text{C}$, unless otherwise noted			
Parameter	Symbol	Value	Unit
		TO-247	
Drain-Source Voltage ($V_{GS} = 0\text{V}$)	V_{DSS}	500	V
Continuous Drain Current	I_D	18	A
Pulsed Drain Current (note1)	I_{DM}	72	A
Gate-Source Voltage	V_{GSS}	± 30	V
Single Pulse Avalanche Energy (note2)	E_{AS}	980	mJ
Avalanche Current (note1)	I_{AS}	14	A
Repetitive Avalanche Energy (note1)	E_{AR}	588	mJ
Power Dissipation ($T_C = 25^\circ\text{C}$)	P_D	160	W
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55~+150	$^\circ\text{C}$

Thermal Resistance			
Parameter	Symbol	Value	Unit
		TO-247	
Thermal Resistance, Junction-to-Case	R_{thJC}	0.6	K/W
Thermal Resistance, Junction-to-Ambient	R_{thJA}	40	

Specifications $T_J = 25^\circ\text{C}$, unless otherwise noted

Parameter	Symbol	Test Conditions	Value			Unit
			Min.	Typ.	Max.	
Static						
Drain-Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	$V_{\text{GS}} = 0\text{V}, I_D = 250\mu\text{A}$	500	--	--	V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{\text{DS}} = 500\text{V}, V_{\text{GS}} = 0\text{V}, T_J = 25^\circ\text{C}$	--	--	1	μA
Gate-Source Leakage	I_{GSS}	$V_{\text{GS}} = \pm 30\text{V}$	--	--	± 100	nA
Gate-Source Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}} = V_{\text{GS}}, I_D = 250\mu\text{A}$	3.0	--	4.0	V
Drain-Source On-Resistance (Note3)	$R_{\text{DS}(\text{on})}$	$V_{\text{GS}} = 10\text{V}, I_D = 9\text{A}$	--	0.28	0.34	Ω
Dynamic						
Input Capacitance	C_{iss}	$V_{\text{GS}} = 0\text{V}, V_{\text{DS}} = 25\text{V}, f = 1.0\text{MHz}$	--	2367	--	pF
Output Capacitance	C_{oss}		--	228	--	
Reverse Transfer Capacitance	C_{rss}		--	15	--	
Total Gate Charge	Q_g	$V_{\text{DD}} = 400\text{V}, I_D = 18\text{A}, V_{\text{GS}} = 10\text{V}$	--	53.4	--	nC
Gate-Source Charge	Q_{gs}		--	10	--	
Gate-Drain Charge	Q_{gd}		--	20	--	
Turn-on Delay Time	$t_{\text{d}(\text{on})}$	$V_{\text{DD}} = 250\text{V}, I_D = 18\text{A}, R_G = 25 \Omega$	--	51.3	--	ns
Turn-on Rise Time	t_r		--	36.5	--	
Turn-off Delay Time	$t_{\text{d}(\text{off})}$		--	232	--	
Turn-off Fall Time	t_f		--	61	--	
Drain-Source Body Diode Characteristics						
Continuous Body Diode Current	I_s	$T_C = 25^\circ\text{C}$	--	--	18	A
Pulsed Diode Forward Current	I_{SM}		--	--	72	
Body Diode Voltage	V_{SD}	$T_J = 25^\circ\text{C}, I_{\text{SD}} = 9\text{A}, V_{\text{GS}} = 0\text{V}$	--	--	1.4	V
Reverse Recovery Time	t_{rr}	$V_{\text{GS}} = 0\text{V}, I_s = 18\text{A}, dI/dt = 100\text{A}/\mu\text{s}$	--	497	--	ns
Reverse Recovery Charge	Q_{rr}		--	4	--	μC

Notes

1. Repetitive Rating: Pulse width limited by maximum junction temperature
2. $L=10\text{mH}, V_{\text{DD}} = 50\text{V}, R_G = 25 \Omega$, Starting $T_J = 25^\circ\text{C}$
3. Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty Cycle $\leq 1\%$

Typical Characteristics $T_J = 25^\circ\text{C}$, unless otherwise noted

Figure 1. Output Characteristics ($T_J = 25^\circ\text{C}$)




Figure 2. Body Diode Forward Voltage




Figure 3. Drain Current vs. Temperature




Figure 4. BV_{DSS} Variation vs. Temperature




Figure 5. Transfer Characteristics





Figure 6. On-Resistance vs. Temperature



Typical Characteristics $T_J = 25^\circ\text{C}$, unless otherwise noted

Figure 7. Capacitance






Figure 8. Gate Charge



**Figure 9. Transient Thermal Impedance
TO-220F**



**Figure 10. Transient Thermal Impedance
TO-220, TO-3P**








Figure A: Gate Charge Test Circuit and Waveform

Figure B: Resistive Switching Test Circuit and Waveform

Figure C: Unclamped Inductive Switching Test Circuit and Waveform


TO-247


Ref.	Dimensions		
	Millimeters		Inches
	Min.	Typ.	Max.
A	4.9		5.4
B	1.6		2.0
C	14.35		15.4
D	0.5		0.8
F	14.4		15.1
G	19.7		20.6
H	15.4		16.2
J	5.3		5.6
K	1.3		1.5
L	2.8		3.3
P	3.7		4.2
S	5.35		5.65
			0.193
			0.063
			0.565
			0.020
			0.567
			0.775
			0.606
			0.209
			0.051
			0.110
			0.146
			0.211
			0.213
			0.079
			0.606
			0.031
			0.594
			0.811
			0.638
			0.220
			0.059
			0.130
			0.165
			0.222